

BSP, NPT, Metric

0 - 0

Metric, Slipfit

0 - 0

Metric, Slipfit

0-0

Metric, Slipfit

0 - 0

Connection


Valves [IN - OUT]





Metric, Slipfit

0 - 0









600

Air Flow Volume [I/min]

800


1000

1200

0

200

Use	Drying of supply air
Material	Aluminium, Acrylic glass, Galvanised steel, Polyamide (PA), Polyvinyl chloride (PVC), FKM, Silica gel orange, Activated carbon
Substance	Hydraulic oil, Gear oil, Biological oil, Vegetable oil, Transformer oil, Insulating oil, AdBlue (Urea), Diesel fuel, Isocyanates, Polyols, Anhydrite / Adhesives, Resins, Amines, PU metal catalysts, Flame retardants, Diethanolamine, Silicone
Refillable	Yes
Application ATEX 2014	No
Offshore Suitable	No
Adsorbent Quantity	Silica gel 0,1 – 4,6 kg
Valves	No
IP Protection Class	IP 63
UV-Resistance	High
Temperature Range	-40°C +80°C
Corrosivity Class	C4
REACH Compliant	Yes
RoHS Compliant	Yes
Customs Tariff Number / Country of Origin	84213925 Germany



Online for download:



Adsorber, Accessories & **Spare Parts** shop.giebel-adsorber.de Order in our Online Shop - 24/7

We would be pleased to advise you personally - by phone, video telephony, email or chat. + 49 79 46 94 44 01-0 | info@giebel-adsorber.de | giebel-adsorber.de