



Mounting Adapter

Field of application | Mounting on horizontal barrel or limited space on hydraulic unit/gearbox



The use of a mounting adapter enables the installation of a GIEBEL adsorber on a horizontal drum and, in case of a given lack of space, on hydraulic units and gears. This is achieved for example by a horizontal or offset installation or elevation by 250mm. The GIEBEL Adsorber can thus be aligned in the desired direction and fixed with the lock nut.

DESIGNED AND PRODUCED IN GERMANY



Barrels & IBC



Hydraulic Power Packs



Gears



REACH COMPLIANT



RoHS COMPLIANT



CE



| | MOA-W | MOA-V | MOA-IAD | MOA-ILK | MOA-TB |
|-------------------|----------|-----------|---------|---------|--------|
| Total Weight [kg] | 0,4 | 1,0 2,0 | 0,6 | 0,7 | 1,0 |
| Width [mm] | 123 50 | 121 292 | 40 | 85/60 | 347 |
| Height [mm] | 78 72 | 104 120 | 254 | 252 | 90 |

| | |
|--|--|
| Use | Mounting in case of lack of space |
| Material | Aluminium, Stainless steel, NBR, FKM |
| System Connection | BSP G 1/2" & 3/4" & 1" male BSP G 1-1/2" & G 2" & M40x1,5 female BC 73mm (DIN 24557) |
| Adsorber Connection | BSP G 3/4" male BSP G 1/2" & 3/4" & 1" female BC 73mm (DIN 24557) |
| Application ATEX 2014 / Offshore Suitable | Yes / Yes |
| Temperature Range | -40°C ... +150°C |
| REACH Compliant | Yes |

Online for download:



Adsorber, Accessories & Spare Parts
shop.giebel-adsorber.de
Order in our Online Shop
24/7

We would be pleased to advise you personally – by phone, video telephony, email or chat.
+ 49 79 46 94 44 01-0 | info@giebel-adsorber.de | giebel-adsorber.de