Oil Separator

Field of application | Protection against oil contamination

The oil separator protects mounted GIEBEL adsorbers from contamination by larger oil particles, on systems with a high oil mist discharge. The air is cooled down by the oil separator and the proportion of evaporating oil particles is considerably reduced, so that humans and environment are effectively protected from harmful oil vapours. In addition, the oil separator prevents oil spillage from the hydraulic tank or gearbox.













Hydraulic Power Packs







	OSD_130	OSD_180_AL	OSD_180_SS
Total weight [kg]	3	0,9	1,6
Diameter [mm]	36	55	55
Height [mm]	143,50	198	200

Use	Protection of the environment from contamination with oil
Material	Aluminium / Brass Nickel-plated (OSD_130, OSD_180_AL) , Stainless Steel / Aluminium (OSD_180_SS), FKM
Adsorber Connection	BSP G 1/2" female (OSB_130) BSP G 1" female (OSD_180_AL, OSD_180_SS)
System Connection	BSP G 1/2" male (OSD_130) BSP G 1" male (OSD_180_AL, OSD_180_SS)
Application ATEX 2014 / Offshore Suitable	Yes / Yes
Temperature Range	-40°C +150°C
REACH Compliant	Yes

Online for download:



Adsorber, Accessories & Spare Parts shop.giebel-adsorber.de Order in our Online Shop – 24/7

We would be pleased to advise you personally + 49 79 46 94 44 01-0 info@giebel-adsorber.de giebel-adsorber.de