



## Protection Adapter

Field of application | Signalling the exchange of a ventilation and venting filters

The protection adapter indicates in connection with a GIEBEL Adsorber the necessary replacement of a filter. If the vacuum is too high, the protection adapter transmits an optical or electronic signal. This accessory is also available with protection valves with an opening pressure of 70 mbar to ensure the exchange of air, even in case of too high negative or positive pressure, if the ventilation filter should be completely blocked.



Storage Tanks



Hydraulic Power Packs



Gears



	PRT-AD_F-ma	PRT-AD_F-el	PRT-AD_F_F-ma_V	PRT-AD_F_V
Total Weight [kg]	0,3   0,8	0,3   0,8	0,5	0,3
Diameter [mm]	97 (x2)	78 (x2)	102 (x2)	60
Height [mm]	69	69	69	49

<b>Use</b>	Signaling filter change
<b>Material</b>	Aluminium / stainless steel
<b>Adsorber Connection</b>	BSP G 1" female
<b>System Connection</b>	BSP G 1" male
<b>Pressure indicator / Protection valves</b>	Optical 100mbar (PRT-AD_F, PRT-AD_F_V / No) Electrical -80mbar AMP plug (PRT-AD_Fel / +/-70mbar)
<b>Temperature Range</b>	-40°C ... +80°C
<b>REACH Compliant</b>	Yes

Online for download:



**Adsorber, Accessories & Spare Parts**  
[giebel-adsorber.com/shop](http://giebel-adsorber.com/shop)  
Order in our Online Shop 24/7

We would be pleased to advise you personally  
**+ 49 79 46 94 44 01-0**  
[info@giebel-adsorber.de](mailto:info@giebel-adsorber.de)  
[giebel-adsorber.com](http://giebel-adsorber.com)