



Wall Mount

Field of application | Flexible mounting of adsorbers



The flexible mounting of an adsorber is possible with this wall bracket even if space on the plant is limited. Available as a screw-on version for concrete walls, with clamping claws for steel beams or as a suspension version for grids, fences, etc., it can be optimally adapted to the conditions on site together with the connection components and a hose. Conversion measures on the system are therefore not necessary.



Storage Tanks



Barrels & IBC



Hydraulic Power Packs



Gears



	WH-HK	WH-OSL	WH-SL	WH-SC2	WH-SC2 KL
Total Weight [kg]	0,5	1,0 1,1	1,5 1,5 1,7	1,7	1,3
Height [mm]	180	350	350	-	-
Length of hose [mm]	-	-	-	2000	1500

Use	Flexible mounting of an adsorber
Material	Stainless steel, PVC, PP, NBR, FKM
Adsorber Connection	BSP G 1" female
System Connection	BSP G 1" female
Application ATEX 2014 / Offshore Suitable	Yes / Yes
Temperature Range	-40°C ... +150°C
REACH Compliant	Yes

Online for download:



Adsorber, Accessories & Spare Parts
shop.giebel-adsorber.de
Order in our Online Shop 24/7

We would be pleased to advise you personally
+ 49 79 46 94 44 01-0 | info@giebel-adsorber.de | giebel-adsorber.de